

台灣製造，車削加工，安裝容易不滲漏，專利雙指針設計，易調整好定位，雷射雕刻刻度精準清晰

F101



F201



F301



F311



F22



F32B



接口尺寸	1/2"	1/2", 3/4"	3/4", 1"	1/2", 3/4", 1"	1/2", 3/4"	1/2", 3/4", 1"
本體材質	PC\PSU	PC\PSU	PC\PSU	PC\PSU	PSU	PSU
浮子材質	SS316, 鈦, Hastelloy C	SS316, 鈦, Hastelloy C	SS316, 鈦, Hastelloy C	不鏽鋼 316	PVC, PP, PVDF, Teflon (依型號固定)	PP
流量範圍	0.2-2.0L/min 0.4 - 4.0 L/min 0.5 - 5.0 L/min 1.0 - 10 L/min 1.5 - 15 L/min 2.0 - 20 L/min	1.0-10L/min 1.5 - 15 L/min 2.0 - 20 L/min 3.0 - 30 L/min 4.0 - 40 L/min 5.0 - 50 L/min	2.0-20L/min 3.0 - 30 L/min 5.0 - 50 L/min 8.0 - 80 L/min 10 - 100 L/min 15 - 150 L/min	23-80LPM 20~100LPM	0.3-3.0L/min(PVC浮子) 0.5 - 5.0 L/min (PVDF 浮子) 0.8 - 8.0 L/min (Teflon 浮子) 1.0 - 10 L/min (Teflon 浮子) 50 - 500 L/hour (Teflon 浮子) 80 - 800 L/hour (PVDF 浮子)	9-18L/min 16 - 32 L/min 30 - 60 L/min 45 - 90 L/min
產品總長	16.4~16.6 cm	18.2~19.5 cm	25~27 cm	19~21 cm	18.3~19.5 cm	18.9~21.1 cm

接頭皆可選基本規格，如內牙，外牙，南亞插管，美規插管，日規插管，歐規插管；承插焊，法蘭等請洽詢

台灣製造，車削加工，安裝容易不滲漏，專利雙指針設計，易調整好定位，雷射雕刻刻度精準清晰

F34



F45



F46



F45M



F201A



F301A



接口尺寸	1/2", 3/4", 1"	1-1/2", 2"	1-1/2", 2"	1-1/2", 2"	1/2", 3/4"	3/4", 1"
本體材質	PSU	PSU	PSU	PSU	PSU	PSU
浮子材質	PP	SS316, Hastelloy C	Teflon, PP, PVDF (依型號固定)	SS316, Hastelloy C	SS316, 鈦, Hastelloy C	PP, 不銹鋼
流量範圍	2.0 - 20 L/min 3.0 - 30 L/min 5.0 - 50 L/min 6.0 - 60 L/min 8.0 - 80 L/min 10 - 100 L/min	10 - 100 L/min 15 - 150 L/min 20 - 200 L/min 25 - 250 L/min 30 - 300 L/min 50 - 450 L/min 100 - 600 L/min	20 - 100 L/min (Teflon 浮子) 30 - 150 L/min (PVDF 浮子) 35 - 200 L/min (PP 浮子) 35 - 250 L/min (PP 浮子)	50 - 300 L/min 50 - 450 L/min 100 - 600 L/min	3.0 - 30 NLPM 5.0 - 50 NLPM 10 - 100 NLPM 20 - 200 NLPM 35 - 350 NLPM 50 - 500 NLPM 100 - 1000 NLPM	40 - 400 NLPM 70 - 700 NLPM 100 - 1000 NLPM
產品總長	24.9~27.1 cm	34.5~35.7 cm	34.5~35.7 cm	34.5~35.7 cm	18.3~19.5 cm	18.9~21.1 cm

可選配檢測感應線
(連接電腦作為流量警報功能)

磁指針設計，適用深色液體

氣體流量計

氣體流量計

接頭皆可選基本規格，如內牙，外牙，南亞插管，美規插管，日規插管，歐規插管；承插焊，法蘭等請洽詢